

Exhibit 7



US010524879B2

(12) **United States Patent**
Kitching et al.

(10) **Patent No.:** **US 10,524,879 B2**
(45) **Date of Patent:** ***Jan. 7, 2020**

(54) **AUTOMATED TREATMENT STAGING FOR TEETH**

(71) Applicant: **ALIGN TECHNOLOGY, INC.**, San Jose, CA (US)

(72) Inventors: **Ian Kitching**, Saratoga, CA (US);
Alexander Dmitriev, Moscow (RU);
Alexey Vishnevskiy, Moscow (RU)

(73) Assignee: **ALIGN TECHNOLOGY, INC.**, San Jose, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **15/834,649**

(22) Filed: **Dec. 7, 2017**

(65) **Prior Publication Data**

US 2018/0092715 A1 Apr. 5, 2018

Related U.S. Application Data

(63) Continuation of application No. 15/086,491, filed on Mar. 31, 2016, now Pat. No. 10,420,631, which is a (Continued)

(51) **Int. Cl.**
A61C 7/00 (2006.01)

(52) **U.S. Cl.**
CPC **A61C 7/002** (2013.01); **A61C 7/00** (2013.01)

(58) **Field of Classification Search**
CPC **A61C 7/002**; **A61C 7/00**; **A61C 3/00**
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,467,432 A 4/1949 Kesling
3,407,500 A 10/1968 Kesling
(Continued)

FOREIGN PATENT DOCUMENTS

AU 3031677 A 5/1979
AU 517102 B2 7/1981
(Continued)

OTHER PUBLICATIONS

AADR. American Association for Dental Research, Summary of Activities, Mar. 20-23, 1980, Los Angeles, CA, p. 195.

(Continued)

Primary Examiner — Cris L. Rodriguez


Assistant Examiner — Mirayda A Aponte

(74) *Attorney, Agent, or Firm* — Wilson Sonsini Goodrich & Rosati

(57) **ABSTRACT**

Apparatus, system, and methods for utilizing one or more computing devices to stage the movement of teeth during an alignment treatment are disclosed. The computing device receives an electronic representation of the patient's teeth in their initial position and an electronic representation of the teeth a final position for each tooth. A route each tooth will travel to reach its final position is determined, and the teeth are scheduled to move according to a movement pattern. Moreover, the schedule of movement takes into account a maximum rate of tooth movement for each tooth, the path of movement for each tooth, the distance each tooth needs to move, any needed tooth staggering, any needed round-tripping or tooth movement slowing. The invention also includes techniques for determining an optimum number of stages for the treatment based on the schedule of movement.

24 Claims, 15 Drawing Sheets



US 10,524,879 B2

Page 2

Related U.S. Application Data

continuation of application No. 13/209,276, filed on Aug. 12, 2011, now Pat. No. 9,326,830, which is a continuation of application No. 11/848,172, filed on Aug. 30, 2007, now Pat. No. 8,038,444.

- (60) Provisional application No. 60/824,024, filed on Aug. 30, 2006, provisional application No. 60/824,022, filed on Aug. 30, 2006.

(58) **Field of Classification Search**

USPC 433/24, 213, 214
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,600,808 A	8/1971	Reeve	5,128,870 A	7/1992	Erdman et al.
3,660,900 A	5/1972	Andrews	5,130,064 A	7/1992	Smalley et al.
3,683,502 A	8/1972	Wallshein	5,131,843 A	7/1992	Hilgers et al.
3,738,005 A	6/1973	Cohen et al.	5,131,844 A	7/1992	Marinaccio et al.
3,860,803 A	1/1975	Levine	5,139,419 A	8/1992	Andreiko et al.
3,916,526 A	11/1975	Schudy	5,145,364 A	9/1992	Martz et al.
3,922,786 A	12/1975	Lavin	5,176,517 A	1/1993	Truax
3,950,851 A	4/1976	Bergersen	5,184,306 A	2/1993	Erdman et al.
3,983,628 A	10/1976	Acevedo	5,186,623 A	2/1993	Breads et al.
4,014,096 A	3/1977	Dellinger	5,257,203 A	10/1993	Riley et al.
4,195,046 A	3/1980	Kesling	5,273,429 A	12/1993	Rekow et al.
4,253,828 A	3/1981	Coles et al.	5,278,756 A	1/1994	Lemchen et al.
4,324,546 A	4/1982	Heitlinger et al.	5,328,362 A	7/1994	Watson et al.
4,324,547 A	4/1982	Arcan et al.	5,338,198 A	8/1994	Wu et al.
4,348,178 A	9/1982	Kurz	5,340,309 A	8/1994	Robertson
4,478,580 A	10/1984	Barrut	5,342,202 A	8/1994	Deshayes
4,500,294 A	2/1985	Lewis	5,368,478 A	11/1994	Andreiko et al.
4,504,225 A	3/1985	Yoshii	5,382,164 A	1/1995	Stern
4,505,673 A	3/1985	Yoshii	5,395,238 A	3/1995	Andreiko et al.
4,526,540 A	7/1985	Dellinger	5,431,562 A	7/1995	Andreiko et al.
4,575,330 A	3/1986	Hull	5,440,326 A	8/1995	Quinn
4,575,805 A	3/1986	Moermann et al.	5,440,496 A	8/1995	Andersson et al.
4,591,341 A	5/1986	Andrews	5,447,432 A	9/1995	Andreiko et al.
4,609,349 A	9/1986	Cain	5,452,219 A	9/1995	Dehoff et al.
4,611,288 A	9/1986	Duret et al.	5,454,717 A	10/1995	Andreiko et al.
4,656,860 A	4/1987	Orthuber et al.	5,456,600 A	10/1995	Andreiko et al.
4,663,720 A	5/1987	Duret et al.	5,474,448 A	12/1995	Andreiko et al.
4,664,626 A	5/1987	Kesling	RE35,169 E	3/1996	Lemchen et al.
4,676,747 A	6/1987	Kesling	5,518,397 A	5/1996	Andreiko et al.
4,742,464 A	5/1988	Duret et al.	5,528,735 A	6/1996	Strasnick et al.
4,755,139 A	7/1988	Abbate et al.	5,533,895 A	7/1996	Andreiko et al.
4,763,791 A	8/1988	Halverson et al.	5,542,842 A	8/1996	Andreiko et al.
4,793,803 A	12/1988	Martz	5,549,476 A	8/1996	Stern
4,798,534 A	1/1989	Breads	5,562,448 A	10/1996	Mushabac
4,836,778 A	6/1989	Baumrind et al.	5,587,912 A	12/1996	Andersson et al.
4,837,732 A	6/1989	Brandestini et al.	5,605,459 A	2/1997	Kuroda et al.
4,850,864 A	7/1989	Diamond	5,607,305 A	3/1997	Andersson et al.
4,850,865 A	7/1989	Napolitano	5,614,075 A	3/1997	Andre, Sr.
4,856,991 A	8/1989	Breads et al.	5,621,648 A	4/1997	Crump
4,877,398 A	10/1989	Kesling	5,645,420 A	7/1997	Bergersen
4,880,380 A	11/1989	Martz	5,645,421 A	7/1997	Slootsky
4,889,238 A	12/1989	Batchelor	5,655,653 A	8/1997	Chester
4,890,608 A	1/1990	Steer	5,683,243 A	11/1997	Andreiko et al.
4,935,635 A	6/1990	O'Harra	5,692,894 A	12/1997	Schwartz et al.
4,936,862 A	6/1990	Walker et al.	5,725,376 A	3/1998	Poirier
4,937,928 A	7/1990	Van Der Zel	5,725,378 A	3/1998	Wang
4,941,826 A	7/1990	Loran et al.	5,733,126 A	3/1998	Andersson et al.
4,964,770 A	10/1990	Steinbichler et al.	5,740,267 A	4/1998	Echerer et al.
4,975,052 A	12/1990	Spencer et al.	5,742,700 A	4/1998	Yoon et al.
4,983,334 A	1/1991	Adell	5,799,100 A	8/1998	Clarke et al.
5,011,405 A	4/1991	Lemchen	5,800,174 A	9/1998	Andersson
5,017,133 A	5/1991	Miura	5,823,778 A	10/1998	Schmitt et al.
5,027,281 A	6/1991	Rekow et al.	5,848,115 A	12/1998	Little et al.
5,035,613 A	7/1991	Breads et al.	5,857,853 A	1/1999	Van Nifterick et al.
5,055,039 A	10/1991	Abbate et al.	5,866,058 A	2/1999	Batchelder et al.
5,059,118 A	10/1991	Breads et al.	5,879,158 A	3/1999	Doyle et al.
5,100,316 A	3/1992	Wildman	5,880,961 A	3/1999	Crump
5,121,333 A	6/1992	Riley et al.	5,880,962 A	3/1999	Andersson et al.
5,125,832 A	6/1992	Kesling	5,934,288 A	8/1999	Avila et al.
			5,957,686 A	9/1999	Anthony
			5,964,587 A	10/1999	Sato
			5,971,754 A	10/1999	Sondhi et al.
			5,975,893 A	11/1999	Chishti et al.
			6,015,289 A	1/2000	Andreiko et al.
			6,044,309 A	3/2000	Honda
			6,049,743 A	4/2000	Baba
			6,062,861 A	5/2000	Andersson
			6,068,482 A	5/2000	Snow
			6,099,314 A	8/2000	Kopelman et al.
			6,123,544 A	9/2000	Cleary
			6,152,731 A	11/2000	Jordan et al.
			6,183,248 B1	2/2001	Chishti et al.
			6,190,165 B1	2/2001	Andreiko et al.
			6,217,325 B1	4/2001	Chishti et al.
			6,217,334 B1	4/2001	Hultgren
			6,244,861 B1	6/2001	Andreiko et al.
			6,309,215 B1 *	10/2001	Phan A61C 7/00 433/24
			6,315,553 B1	11/2001	Sachdeva et al.

US 10,524,879 B2

Page 3

(56)

References Cited

U.S. PATENT DOCUMENTS

6,318,994	B1	11/2001	Chishti et al.	
6,322,359	B1	11/2001	Jordan et al.	
6,350,120	B1	2/2002	Sachdeva et al.	
6,382,975	B1	5/2002	Poirier	
6,398,548	B1	6/2002	Muhammad et al.	
6,402,707	B1	6/2002	Ernst	
6,409,504	B1	6/2002	Jones et al.	
6,471,511	B1 *	10/2002	Chishti	A61C 7/00 433/24
6,482,298	B1	11/2002	Bhatnagar	
6,514,074	B1	2/2003	Chishti et al.	
6,524,101	B1	2/2003	Phan et al.	
6,554,611	B2	4/2003	Chishti et al.	
6,572,372	B1	6/2003	Phan et al.	
6,629,840	B2	10/2003	Chishti et al.	
6,682,346	B2	1/2004	Chishti et al.	
6,705,863	B2	3/2004	Phan et al.	
6,722,880	B2	4/2004	Chishti et al.	
6,729,876	B2	5/2004	Chishti et al.	
7,063,532	B1	6/2006	Jones et al.	
7,331,783	B2	2/2008	Chishti et al.	
7,377,778	B2	5/2008	Chishti et al.	
7,435,083	B2	10/2008	Chishti et al.	
7,578,674	B2	8/2009	Chishti et al.	
7,637,740	B2	12/2009	Knopp	
7,658,610	B2	2/2010	Knopp	
7,819,659	B2	10/2010	Wen	
7,844,356	B2	11/2010	Matov et al.	
7,844,429	B2	11/2010	Matov et al.	
7,904,307	B2	3/2011	Abolfathi et al.	
8,038,444	B2	10/2011	Kitching et al.	
9,326,830	B2	5/2016	Kitching et al.	
2002/0006597	A1	1/2002	Andreiko et al.	
2002/0064746	A1 *	5/2002	Muhammad	A61C 7/00 433/24
2003/0009252	A1	1/2003	Pavlovskaja et al.	
2003/0139834	A1	7/2003	Nikolskiy et al.	
2003/0224311	A1	12/2003	Cronauer	
2004/0128010	A1	7/2004	Pavlovskaja et al.	
2004/0137400	A1 *	7/2004	Chishti	A61C 7/00 433/24
2005/0055118	A1	3/2005	Nikolskiy et al.	
2006/0275736	A1	12/2006	Wen et al.	
2012/0035901	A1	2/2012	Kitching et al.	
2016/0206402	A1	7/2016	Kitching et al.	

FOREIGN PATENT DOCUMENTS

AU	5598894	A	6/1994
CA	1121955	A	4/1982
DE	2749802	A1	5/1978
DE	69327661	T2	7/2000
EP	0091876	A1	10/1983
EP	0299490	A2	1/1989
EP	0376873	A2	7/1990
EP	0490848	A2	6/1992
EP	0541500	A1	5/1993
EP	0667753	B1	1/2000
EP	0774933	B1	12/2000
EP	0731673	B1	5/2001
ES	463897	A1	1/1980
FR	2369828	A1	6/1978
FR	2652256	A1	3/1991
GB	1550777	A	8/1979
JP	S5358191	A	5/1978
JP	H0428359	A	1/1992
JP	H08508174	A	9/1996
WO	WO-9008512	A1	8/1990
WO	WO-9104713	A1	4/1991
WO	WO-9410935	A1	5/1994
WO	WO-9832394	A1	7/1998
WO	WO-9844865	A1	10/1998
WO	WO-9858596	A1	12/1998

OTHER PUBLICATIONS

Alcaniz, et al., "An Advanced System for the Simulation and Planning of Orthodontic Treatments," Karl Heinz Hohne and Ron Kikinis (eds.), Visualization in Biomedical Computing, 4th Intl. Conf., VBC '96, Hamburg, Germany, Sep. 22-25, 1996, Springer-Verlag, pp. 511-520.

Alexander et al., "The DigiGraph Work Station Part 2 Clinical Management," JCO, pp. 402-407 (Jul. 1990).

Altschuler, "3D Mapping of Maxillo-Facial Prosthesis," AADR Abstract #607, 2 pages total, (1980).

Altschuler et al., "Analysis of 3-D Data for Comparative 3-D Serial Growth Pattern Studies of Oral-Facial Structures," AADR Abstracts, Program and Abstracts of Papers, 57th General Session, IADR HP Annual Session, Mar. 29, 1979-Apr. 1, 1979, New Orleans Marriot, Journal of Dental Research, vol. 58, Jan. 1979, Special Issue A, p. 221.

Altschuler et al., "Laser Electro-Optic System for Rapid Three-Dimensional (3D) Topographic Mapping of Surfaces," Optical Engineering, 20(6):953-961 (1981).

Altschuler et al., "Measuring Surfaces Space-Coded by a Laser-Projected Dot Matrix," SPIE Imaging Applications for Automated Industrial Inspection and Assembly, vol. 182, p. 187-191 (1979).

Andersson et al., "Clinical Results with Titanium Crowns Fabricated with Machine Duplication and Spark Erosion," Acta Odontol. Scand., 47:279-286 (1989).

Andrews, The Six Keys to Optimal Occlusion Straight Wire, Chapter 3, pp. 13-24 (1989).

Bartels, et al., An Introduction to Splines for Use in Computer Graphics and Geometric Modeling, Morgan Kaufmann Publishers, pp. 422-425 (1987).

Baumrind, "A System for Craniofacial Mapping Through the Integration of Data from Stereo X-Ray Films and Stereo Photographs," an invited paper submitted to the 1975 American Society of Photogram Symposium on Close-Range Photogram Systems, University of Ill., Aug. 26-30, 1975, pp. 142-166.

Baumrind et al., "A Stereophotogrammetric System for the Detection of Prosthesis Loosening in Total Hip Arthroplasty," NATO Symposium on Applications of Human Biostereometrics, Jul. 9-13, 1978, SPIE, vol. 166, pp. 112-123.

Baumrind et al., "Mapping the Skull in 3-D," reprinted from J. Calif. Dent. Assoc., 48(2), 11 pages total, (1972 Fall Issue).

Baumrind, "Integrated Three-Dimensional Craniofacial Mapping: Background, Principles, and Perspectives," Semin. in Orthod., 7(4):223-232 (Dec. 2001).

Begole et al., "A Computer System for the Analysis of Dental Casts," The Angle Orthod., 51(3):253-259 (Jul. 1981).

Bernard et al., "Computerized Diagnosis in Orthodontics for Epidemiological Studies: A Progress Report," Abstract, J. Dental Res. Special Issue, vol. 67, p. 169, paper presented at International Association for Dental Research 66th General Session, Mar. 9-13, 1988, Montreal, Canada.

Bhatia et al., "A Computer-Aided Design for Orthognathic Surgery," Br. J. Oral Maxillofac. Surg., 22:237-253 (1984).

Biggerstaff, "Computerized Diagnostic Setups and Simulations," Angle Orthod., 40(1):28-36 (Jan. 1970).

Biggerstaff et al., "Computerized Analysis of Occlusion in the Postcanine Dentition," Am. J. Orthod., 61(3): 245-254 (Mar. 1972).

Biostar Opeation & Training Manual. Great Lakes Orthodontics, Ltd. 199 Fire Tower Drive, Tonawanda, New York. 14150-5890, 20 pages total (1990).

Blu, et al., "Linear interpolation revitalized", IEEE Trans. Image Proc., 13(5):710-719 (May 2004).

Bourke, "Coordinate System Transformation," (Jun. 1996), p. 1, retrieved from the Internet Nov. 5, 2004, URL< <http://astronomy.swin.edu.au/~pbourke/projection/coords>>.

Boyd et al., "Three Dimensional Diagnosis and Orthodontic Treatment of Complex Malocclusions With the Invisalipn Appliance," Semin. Orthod., 7(4):274-293 (Dec. 2001).

Brandestini et al., "Computer Machined Ceramic Inlays: In Vitro Marginal Adaptation," J. Dent. Res. Special Issue, Abstract 305, vol. 64, p. 208 (1985).

US 10,524,879 B2

Page 4

(56) **References Cited**

OTHER PUBLICATIONS

- Brook et al., "An Image Analysis System for the Determination of Tooth Dimensions from Study Casts: Comparison with Manual Measurements of Mesio-distal Diameter," *J. Dent. Res.*, 65(3):428-431 (Mar. 1986).
- Burstone et al., Precision Adjustment of the Transpalatal Lingual Arch: Computer Arch Form in Predetermination, *Am. Journal of Orthodontics*, vol. 79, No. 2 (Feb. 1981), pp. 115-133.
- Burstone (interview), "Dr. Charles J. Burstone on The Uses of the Computer in Orthodontic Practice (Part 1)," *J. Clin. Orthod.*, 13(7):442-453 (Jul. 1979).
- Burstone (interview), "Dr. Charles J. Burstone on The Uses of the Computer in Orthodontic Practice (Part 2)," *J. Clin. Orthod.*, 13(8):539-551 (Aug. 1979).
- Cardinal Industrial Finishes, Powder Coatings information posted at < <http://www.cardinalpaint.com> > on Aug. 25, 2000, 2 pages.
- Carnaghan, "An Alternative to Holograms for the Portrayal of Human Teeth," 4th Int'l. Conf. on Holographic Systems, Components and Applications, Sep. 15, 1993, pp. 228-231.
- Chaconas et al., "The DigiGraph Work Station, Part 1, Basic Concepts," *JCO*, pp. 360-367 (Jun. 1990).
- Chafetz et al., "Subsidence of the Femoral Prosthesis, A Stereophotogrammetric Evaluation," *Clin. Orthop. Relat. Res.*, No. 201, pp. 60-67 (Dec. 1985).
- Chiappone, (1980). Constructing the Gnathologic Setup and Positioner, *J. Clin. Orthod*, vol. 14, pp. 121-133.
- Cottingham, (1969). Gnathologic Clear Plastic Positioner, *Am. J. Orthod*, vol. 55, pp. 23-31.
- Crawford, "CAD/CAM in the Dental Office: Does It Work?," *Canadian Dental Journal*, vol. 57, No. 2, pp. 121-123 (Feb. 1991).
- Crawford, "Computers in Dentistry: Part 1 CAD/CAM: The Computer Moves Chairside," Part 2 F. Duret—A Man with a Vision, "Part 3 The Computer Gives New Vision—Literally," Part 4 Bytes 'N Bites—The Computer Moves from the Front Desk to the Operatory, *Canadian Dental Journal*, vol. 54 (9), pp. 661-666 (1988).
- Crooks, "CAD/CAM Comes to USC," *USC Dentistry*, pp. 14-17 (Spring 1990).
- Cureton, Correcting Malaligned Mandibular Incisors with Removable Retainers, *J. Clin. Orthod*, vol. 30, No. 7 (1996) pp. 390-395.
- Curry et al., "Integrated Three-Dimensional Craniofacial Mapping at the Craniofacial Research Instrumentation Laboratory/University of the Pacific," *Semin. Orthod.*, 7(4):258-265 (Dec. 2001).
- Cutting et al., "Three-Dimensional Computer-Assisted Design of Craniofacial Surgical Procedures: Optimization and Interaction with Cephalometric and CT-Based Models," *Plast. 77(6):877-885* (Jun. 1986).
- DCS Dental AG, "The CAD/CAM 'DCS Titan System' for Production of Crowns/Bridges," *DSC Production AG*, pp. 1-7 (Jan. 1992).
- Definition for gingiva. Dictionary.com p. 1-3. Retrieved from the internet Nov. 5, 2004 < <http://reference.com/search/search?q=gingiva> >.
- Defranco et al., "Three-Dimensional Large Displacement Analysis of Orthodontic Appliances," *J. Biomechanics*, 9:793-801 (1976).
- Dental Institute University of Zurich Switzerland, Program for International Symposium JD on Computer Restorations: State of the Art of the CEREC-Method, May 1991, 2 pages total.
- Dentrac Corporation, Dentrac document, pp. 4-13 (1992).
- Dent-X posted on Sep. 24, 1998 at < <http://www.dent-x.com/DentSim.htm> >, 6 pages.
- Doyle, "Digital Dentistry," *Computer Graphics World*, pp. 50-52, 54 (Oct. 2000).
- DuraClear™ product information, Allesee Orthodontic Appliances-Pro Lab, 1 page (1997).
- Duret et al., "CAD/CAM Imaging in Dentistry," *Curr. Opin. Dent.*, 1:150-154 (1991).
- Duret et al., "CAD-CAM in Dentistry," *J. Am. Dent. Assoc.* 117:715-720 (Nov. 1988).
- Duret, "The Dental CAD/CAM, General Description of the Project," Hennson International Product Brochure, 18 pages total, Jan. 1986.
- Duret, "Vers Une Prothese Informatisee," (English translation attached), *Tonus*, vol. 75, pp. 55-57 (Nov. 15, 1985).
- Economides, "The Microcomputer in the Orthodontic Office," *JCO*, pp. 767-772 (Nov. 1979).
- Elsasser, Some Observations on the History and Uses of the Kesling Positioner, *Am. J. Orthod.* (1950) 36:368-374.
- English translation of Japanese Laid-Open Publication No. 63-11148 to inventor T. Ozukuri (Laid-Open on Jan. 18, 1998) pp. 1-7.
- Felton et al., "A Computerized Analysis of the Shape and Stability of Mandibular Arch Form," *Am. J. Orthod. Dentofacial Orthop.*, 92(6):478-483 (Dec. 1987).
- Friede et al., "Accuracy of Cephalometric Prediction in Orthognathic Surgery," *Abstract of Papers, J. Dent. Res.*, 70:754-760 (1987).
- Futterling et al., "Automated Finite Element Modeling of a Human Mandible with Dental Implants," *JS WSCG '98—Conference Program*, retrieved from the Internet < http://wscg.zcu.cz/wscg98/papers98/Strasser_98.pdf >, 8 pages.
- Gao et al., "3-D element Generation for Multi-Connected Complex Dental and Mandibular Structure," *Proc. Intl Workshop on Medical Imaging and Augmented Reality*, pp. 267-271 (Jun. 12, 2001).
- Gim-Alldent Deutschland, "Das DUX System: Die Technik," 2 pages total (2002).
- Gottlieb et al., "JCO Interviews Dr. James A. McNamara, Jr., on the Frankel Appliance: Part 2: Clinical 1-1 Management," *J. Clin. Orthod.*, 16(6):390-407 (Jun. 1982).
- Grayson, "New Methods for Three Dimensional Analysis of Craniofacial Deformity, Symposium: JW Computerized Facial Imaging in Oral and Maxillofacial Surgery," *AAOMS*, 3 pages total, (Sep. 13, 1990).
- Guess et al., "Computer Treatment Estimates in Orthodontics and Orthognathic Surgery," *JCO*, pp. 262-28 (Apr. 1989).
- Heaven et al., "Computer-Based Image Analysis of Artificial Root Surface Caries," *Abstracts of Papers, J. Dent. Res.*, 70:528 (Apr. 17-21, 1991).
- Highbeam Research, "Simulating Stress Put on Jaw," Tooling & Production [online], Nov. 1996, n pp. 1-2, retrieved from the Internet on Nov. 5, 2004, URL <http://static.highbeam.com/t/toolingampproduction/november011996/simulatingstressputonfa...>
- Hikage, "Integrated Orthodontic Management System for Virtual Three-Dimensional Computer Graphic Simulation and Optical Video Image Database for Diagnosis and Treatment Planning", *Journal of Japan KA Orthodontic Society*, Feb. 1987, English translation, pp. 1-38, Japanese version, 46(2), pp. 248-269 (60 pages total).
- Hoffmann, et al., "Role of Cephalometry for Planning of Jaw Orthopedics and Jaw Surgery Procedures," (Article Summary in English, article in German), *Informatbnen*, pp. 375-396 (Mar. 1991).
- Hojjat et al., "Three-Dimensional Finite Element Analysis of Glass-Ceramic Dental Crowns," *J. Biomech.*, 23(11):1157-1166 (1990).
- Huckins, "CAD-CAM Generated Mandibular Model Prototype from MRI Data," *AAOMS*, p. 96 (1999).
- Important Tip About Wearing the Red White & Blue Active Clear Retainer System, Allesee Orthodontic Appliances-Pro Lab, 1 page (1998).
- JCO Interviews, Craig Andreiko, DDS, MS on the Elan and Orthos Systems, *JCO*, pp. 459-468 (Aug. 1994).
- JCO Interviews, Dr. Homer W. Phillips on Computers in Orthodontic Practice, Part 2, *JCO*. 1997; 1983:819-831.
- Jerrold, "The Problem, Electronic Data Transmission and the Law," *AJO-DO*, pp. 478-479 (Apr. 1988).
- Jones et al., "An Assessment of the Fit of a Parabolic Curve to Pre- and Post-Treatment Dental Arches," *Br. J. Orthod.*, 16:85-93 (1989).
- JP Faber et al., "Computerized Interactive Orthodontic Treatment Planning," *Am. J. Orthod.*, 73(1):36-46 (Jan. 1978).
- Kamada et al., Case Reports on Tooth Positioners Using LTV Vinyl Silicone Rubber, *J. Nihon University School of Dentistry* (1984) 26(1): 11-29.

US 10,524,879 B2

Page 5

(56)

References Cited

OTHER PUBLICATIONS

- Kamada et al., Construction of Tooth Positioners with LTV Vinyl Silicone Rubber and Some Case Reports, *J. Nihon University School of Dentistry* (1982) 24(1):1-27.
- Kanazawa et al., "Three-Dimensional Measurements of the Occlusal Surfaces of Upper Molars in a Dutch Population," *J. Dent Res.*, 63(11):1298-1301 (Nov. 1984).
- Kesling, Coordinating the Predetermined Pattern and Tooth Positioner with Conventional Treatment, *KN Am. J. Orthod. Oral Surg.* (1946) 32:285-293.
- Kesling et al., The Philosophy of the Tooth Positioning Appliance, *American Journal of Orthodontics and Oral surgery*, 1945; 31:297-304.
- Kleeman et al., The Speed Positioner, *J. Clin. Orthod.* (1996) 30:673-680.
- Kochanek, "Interpolating Splines with Local Tension, Continuity and Bias Control," *Computer Graphics*, 18(3):33-41 (Jul. 1984).
- KM Oral Surgery (1945) 31 :297-30.
- Kunii et al., "Articulation Simulation for an Intelligent Dental Care System," *Displays* 15:181-188 (1994).
- Kuroda et al., Three-Dimensional Dental Cast Analyzing System Using Laser Scanning, *Am. J. Orthod. Dentofac. Orthop.* (1996) 110:365-369.
- Laurendeau, et al., "A Computer-Vision Technique for the Acquisition and Processing of 3-D Profiles of 7 KR Dental Imprints: An Application in Orthodontics," *IEEE Transactions on Medical Imaging*, 10(3):453-461 (Sep. 1991).
- Leinfelder, et al., "A New Method for Generating Ceramic Restorations: a CAD-CAM System," *J. Am. 1-1 Dent. Assoc.*, 118(6):703-707 (Jun. 1989).
- Manetti, et al., "Computer-Aided Cefalometry and New Mechanics in Orthodontics," (Article Summary in English, article in German), *Fortschr Kieferorthop.* 44, 370-376 (Nr. 5), 1983.
- McCann, "Inside the ADA," *J. Amer. Dent. Assoc.*, 118:286-294 (Mar. 1989).
- McNamara et al., "Invisible Retainers," *J. Cfin. Orthod.*, pp. 570-578 (Aug. 1985).
- McNamara et al., *Orthodontic and Orthopedic Treatment in the Mixed Dentition*, Needham Press, pp. 347-353 (Jan. 1993).
- Moermann et al., "Computer Machined Adhesive Porcelain Inlays: Margin Adaptation after Fatigue Stress," *IADR Abstract* 339, *J. Dent. Res.*, 66(a):763 (1987).
- Moles, "Correcting Mild Malalignments—As Easy As One, Two, Three," *AOA/Pro Corner*, vol. 11, No. 1, 2 pages (2002).
- Mormann et al., "Marginale Adaptation von adhasiven Porzellaninlays in vitro," *Separatdruck aus: Schweiz. Mschr. Zahnmed.* 95: 1118-1129, 1985.
- Nahoum, "The Vacuum Formed Dental Contour Appliance," *N. Y. State Dent. J.*, 30(9):385-390 (Nov. 1964).
- Nash, "CEREC CAD/CAM Inlays: Aesthetics and Durability in a Single Appointment," *Dent. Today*, 9(8):20, 22-23 (Oct. 1990).
- Nishiyama et al., "A New Construction of Tooth Repositioner by LTV Vinyl Silicone Rubber," *J. Nihon Univ. Sch. Dent.*, 19(2):93-102 (1977).
- Paul et al., "Digital Documentation of Individual Human Jaw and Tooth Forms for Applications in Orthodontics, Oral Surgery and Forensic Medicine" *Proc. of the 24th Annual Conf. of the IEEE Industrial Electronics Society (IECON '98)*, Sep. 4, 1998, pp. 2415-2418.
- Pinkham, "Foolish Concept Propels Technology," *Dentist*, 3 pages total, Jan./Feb. 1989.
- Pinkham, "Inventor's CAD/CAM May Transform Dentistry," *Dentist*, 3 pages total, Sep. 1990.
- Ponitz, "Invisible Retainers," *Am. J. Orthod.*, 59(3):266-272 (Mar. 1971).
- Procera Research Projects, "PROCERA Research Projects 1993—Abstract Collection," pp. 3- 7; 28 (1993).
- Proffit et al., *Contemporary Orthodontics*, (Second Ed.), Chapter 15, Mosby Inc., pp. 470-533 (Oct. 1993).
- Raintree Essix & ARS Materials, Inc., Raintree Essix, Technical Magazine Table of contents and Essix Appliances, < [http:// www.essix.com/magazine/default.html](http://www.essix.com/magazine/default.html)> Aug. 13, 1997.
- Redmond et al., "Clinical Implications of Digital Orthodontics," *Am. J. Orthod. Dentofacial Orthop.*, 117(2):240-242 (2000).
- Rekow, "A Review of the Developments in Dental CAD/CAM Systems," (contains references to Japanese efforts and content of the papers of particular interest to the clinician are indicated with a one line summary of their content in the bibliography), *Curr. Opin. Dent.*, 2:25-33 (Jun. 1992).
- Rekow, "CAD/CAM in Dentistry: A Historical Perspective and View of the Future," *J. Can. Dent. Assoc.*, 58(4):283, 287-288 (Apr. 1992).
- Rekow, "Computer-Aided Design and Manufacturing in Dentistry: A Review of the State of the Art," *J. Prosthet. Dent.*, 58(4):512-516 (Oct. 1987).
- Rekow, "Dental CAD-CAM Systems: What is the State of the Art?", *J. Amer. Dent. Assoc.*, 122:43-48 1991.
- Rekow et al., "CAD/CAM for Dental Restorations—Some of the Curious Challenges," *IEEE Trans. Biomed. Eng.*, 38(4):344-345 (Apr. 1991).
- Rekow et al., "CAD/CAM for Dental Restorations—Some of the Curious Challenges," *IEEE Trans. Biomed. Eng.*, 38(4):314-318 (Apr. 1991).
- Rekow et al., "Comparison of Three Data Acquisition Techniques for 3-D Tooth Surface Mapping," *Annual International Conference of the IEEE Engineering in Medicine and Biology Society*, 13(1):344-345 1991.
- Rekow, "Feasibility of an Automated System for Production of Dental Restorations, Ph.D. Thesis," Univ. of Minnesota, 244 pages total, Nov. 1988.
- Richmond et al., "The Development of a 3D Cast Analysis System," *Br. J. Orthod.*, 13(1):53-54 (Jan. 1986).
- Richmond et al., "The Development of the PAR Index (Peer Assessment Rating): Reliability and Validity," *Eur. J. Orthod.*, 14:125-139 (1992).
- Richmond, "Recording the Dental Cast in Three Dimensions," *Am. J. Orthod. Dentofacial Orthop.*, 92(3):199-206 (Sep. 1987).
- Rudge, "Dental Arch Analysis: Arch Form, A Review of the Literature," *Eur. J. Orthod.*, 3(4):279-284 1981.
- Sakuda et al., "Integrated Information-Processing System in Clinical Orthodontics: An Approach with Use of a Computer Network System," *Am. J. Orthod. Dentofacial Orthop.*, 101(3): 210-220 (Mar. 1992).
- Schellhas et al., "Three-Dimensional Computed Tomography in Maxillofacial Surgical Planning," *Arch. Otolamp!. Head Neck Surg.*, 114:438-442 (Apr. 1988).
- Schroeder et al., Eds. *The Visual Toolkit*, Prentice Hall PTR, New Jersey (1998) Chapters 6, 8 & 9, (pp. 153-210, 309-354, and 355-428, respectively).
- Shilliday, (1971). Minimizing finishing problems with the mini-positioner, *Am. J. Orthod.* 59:596-599.
- Siemens, "CEREC—Computer-Reconstruction," *High Tech in der Zahnmedizin*, 14 pages total (2004).
- Sinclair, "The Readers' Corner," *J. Clin. Orthod.*, 26(6):369-372 (Jun. 1992).
- Sirona Dental Systems GmbH, CEREC 3D, Manuel utilisateur, Version 2.0X (in French), 2003, 114 pages total.
- Stoll et al., "Computer-aided Technologies in Dentistry," (article summary in English, article in German), *Dtsch Zahna'rztl Z* 45, pp. 314-322 (1990).
- Sturman, "Interactive Keyframe Animation of 3-D Articulated Models," *Proceedings Graphics Interface '84*, May-Jun. 1984, pp. 35-40.
- The Choice Is Clear: Red, White & Blue . . . The Simple, Affordable, No-Braces Treatment, Allesee HI Orthodontic Appliances—Pro Lab product information for doctors. <http://ormco.com/aoa/applianceservices/RWB/doctor.html>, 5 pages (May 19, 2003).
- The Choice Is Clear: Red, White & Blue . . . The Simple, Affordable, No-Braces Treatment, Allesee HJ Orthodontic Appliances—Pro Lab product information for patients, < <http://ormco.com/aoa/applianceservices/RWB/patients.html>>, 2 pages (May 19, 2003).

US 10,524,879 B2

Page 6

(56)

References Cited

OTHER PUBLICATIONS

The Choice Is Clear: Red, White & Blue . . . The Simple, Affordable, No-Braces Treatment, Allesee Orthodontic Appliances—Pro Lab product information, 6 pages (2003).

The Red, White & Blue Way to Improve Your Smile! Allesee Orthodontic Appliances—Pro Lab product information for patients, 2 pages 1992.

Truax L., “Truax Clasp-Less(TM) Appliance System,” *Funct. Orthod.*, 9(5):22-4, 26-8 (Sep.-Oct. 1992).

Tru-Tain Orthodontic & Dental Supplies, Product Brochure, Rochester, Minnesota 55902, 16 pages total (1996).

U.S. Department of Commerce, National Technical Information Service, “Automated Crown Replication Using Solid Photography SM,” Solid Photography Inc., Melville NY, Oct. 1977, 20 pages total.

U.S. Department of Commerce, National Technical Information Service, “Holodontography: An Introduction to Dental Laser Holography,” School of Aerospace Medicine Brooks AFB Tex, Mar. 1973, 37 pages total.

U.S. Appl. No. 60/050,342, filed Jun. 20, 1997, 41 pages total.

Van Der Linden, “A New Method to Determine Tooth Positions and Dental Arch Dimensions,” *J. Dent. Res.*, 51(4):1104 (Jul.-Aug. 1972).

Van Der Linden et al., “Three-Dimensional Analysis of Dental Casts by Means of the Optocom,” *J. Dent. Res.*, p. 1100 (Jul.-Aug. 1972).

Van Der Zel, “Ceramic-Fused-to-Metal Restorations with a New CAD/CAM System,” *Quintessence Int.*, 24(11):769-778 (1993).

Varady et al., “Reverse Engineering of Geometric Models—An Introduction,” *Computer-Aided Design*, 29(4):255-268, 1997.

Verstreken et al., “An Image-Guided Planning System for Endosseous Oral Implants,” *IEEE Trans. Med. Imaging*, 17(5):842-852 (Oct. 1998).

Warunek et al., Physical and Mechanical Properties of Elastomers in Orthodontic Positioners, *Am J. Orthod. Dentofac. Orthop.*, vol. 95, No. 5, (May 1989) pp. 399-400.

Warunek et al., Clinical Use of Silicone Elastomer Appliances, *JCO* (1989) XXIII(10):694-700.

Wells, Application of the Positioner Appliance in Orthodontic Treatment, *Am. J. Orthodont.* (1970) 58:351-366.

Williams, “Dentistry and CAD/CAM: Another French Revolution,” *J. Dent. Practice Admin.*, pp. 2-5 (Jan./Mar. 1987).

Williams, “The Switzerland and Minnesota Developments in CAD/CAM,” *J. Dent. Practice Admin.*, pp. 50-55 (Apr./Jun. 1987).

Wishan, “New Advances in Personal Computer Applications for Cephalometric Analysis, Growth Prediction, Surgical Treatment Planning and Imaging Processing,” Symposium: Computerized Facial Imaging in Oral and Maxillofacial Surgery Presented on Sep. 13, 1990.

WSCG’98—Conference Program, “The Sixth International Conference in Central Europe on Computer Graphics and Visualization ’98,” Feb. 9-13, 1998, pp. 1-7, retrieved from the Internet on Nov. 5, 2004, URL: <<http://wscg.zcu.cz/wscg98/wscg98.h>>.

Xia et al., “Three-Dimensional Virtual-Reality Surgical Planning and Soft-Tissue Prediction for Orthognathic Surgery,” *IEEE Trans. Inf. Technol. Biomed.*, 5(2):97-107 (Jun. 2001).

Yamamoto et al., “Optical Measurement of Dental Cast Profile and Application to Analysis of Three-Dimensional Tooth Movement in Orthodontics,” *Front. Med. Biol. Eng.*, 1(2):119-130 (1988).

Yamamoto et al., “Three-Dimensional Measurement of Dental Cast Profiles and Its Applications to Orthodontics,” *Conf. Proc. IEEE Eng. Med. Biol. Soc.*, 12(5):2051-2053 (1990).

Yamany et al., “A System for Human Jaw Modeling Using Intra-Oral Images,” *Proc. of the 20th Annual Conf. of the IEEE Engineering in Medicine and Biology Society*, Nov. 1, 1998, vol. 2, pp. 563-566.

Yoshii, “Research on a New Orthodontic Appliance: The Dynamic Positioner (D.P.); I. The D.P. Concept and Implementation of Transparent Silicone Resin (Orthocon),” *Nippon Dental Review*, 452:61-74 (Jun. 1980).

Yoshii, “Research on a New Orthodontic Appliance: The Dynamic Positioner (D.P.); II. The D.P. Manufacturing Procedure and Clinical Applications,” *Nippon Dental Review*, 454:107-130 (Aug. 1980).

Yoshii, “Research on a New Orthodontic Appliance: The Dynamic Positioner (D.P.); III. The General Concept of the D.P. Method and Its Therapeutic Effect, Part 1, Dental and Functional Reversed Occlusion Case Reports,” *Nippon Dental Review*, 457:146-164 (Nov. 1980).

Yoshii, “Research on a New Orthodontic Appliance: The Dynamic Positioner (D.P.); III.—The General Concept of the D.P. Method and Its Therapeutic Effect, Part 2. Skeletal Reversed Occlusion Case Reports,” *Nippon Dental Review*, 458:112-129 (Dec. 1980).

You May Be a Candidate for This Invisible No-Braces Treatment, Allesee Orthodontic Appliances—Pro Lab product information for patients, 2 pages (2002).

* cited by examiner

U.S. Patent

Jan. 7, 2020

Sheet 1 of 15

US 10,524,879 B2




FIG. 1A




FIG. 1B




FIG. 1C




FIG. 1D




FIG. 2A




FIG. 2B

300

STAGE	7(31)	6(30)	5(29)	4(28)	3(27)	2(26)	1(25)	1(24)	2(23)	3(22)	4(21)	5(20)	6(19)	7(18)
0														
1														
2														
3														
4														
5														
6														
7														
8														

FIG. 3




FIG. 4




FIG. 5





FIG. 6A






FIG. 7




FIG. 8




FIG. 9




FIG. 10A

U.S. Patent

Jan. 7, 2020

Sheet 14 of 15

US 10,524,879 B2

1000

1010

1030

1020

Stg	7(2)	6(3)	5(4)	4(5)	3(6)	2(7)	1(8)	1(9)	2(10)	3(11)	4(12)	5(13)	6(14)	7(15)	8(16)
8	.29	.29	.23	.27							.17	.15			
9		.30	.23	.27							.17	.15			
10		.30	.23	.27						.31	.17	.14			
11			.23	.27						.30	.17	.14			
12			.23	.27	.23	.22	.09	.24	.30	.17					
13				.28	.23	.22	.09	.24	.30	.17					
14				.28	.23	.23	.10	.24	.30						
15				.28	.23	.23	.10	.24	.30						
16				.28	.23	.23	.10	.24	.30						
17					.23	.23	.10	.24							
18					.23	.23	.10	.24							
19					.23	.23	.10	.24							
20					.23	.23	.10	.24							
21					.23	.23	.10	.24							
22					.16	.23	.10	.18							
23					.16	.23	.10	.18							
24					.16	.24	.10	.18							
25					.16	.24	.10	.18							
26					.16	.24	.10	.18							
27					.16	.24	.10	.18							
28					.15	.24									
29					.15	.24									
30					.15	.24									
31					.15	.24									
32						.21	.12								
33						.21	.12								

Key Frame Move Dist Collision Space Overcorrection Translation (mm) Rotation (deg)

FIG. 10B




FIG. 11

US 10,524,879 B2

1

**AUTOMATED TREATMENT STAGING FOR
TEETH****CROSS-REFERENCE**

This application is a continuation of U.S. patent application Ser. No. 15/086,491, filed Mar. 31, 2016, now U.S. Pat. No. 10,420,631, issued Sep. 24, 2019, which is a continuation of U.S. patent application Ser. No. 13/209,276, filed Aug. 12, 2011, now U.S. Pat. No. 9,326,830, issued May 3, 2016, which is a continuation of U.S. patent application Ser. No. 11/848,172, filed Aug. 30, 2007, now U.S. Pat. No. 8,038,444, issued Oct. 18, 2011, which claims the benefit of U.S. Provisional Patent Application No. 60/824,022, filed Aug. 30, 2006, and U.S. Provisional Patent Application No. 60/824,024, filed Aug. 30, 2006, the entire contents of which are hereby incorporated by reference.

BACKGROUND**Field of the Invention**

The present invention is related generally to the field of orthodontics, and more particularly to staging a path of movement for correcting the position of one or more teeth.

Related Art

One objective of orthodontics is to move a patient's teeth to positions where the teeth function optimally and aesthetically. Conventionally, braces are applied to the teeth of a patient by an orthodontist. The braces exert continual force on the teeth and gradually urge the teeth to their respective ideal position. The orthodontist does this by adjusting the braces over time to move the teeth toward their final destination.

Apparatus, systems, and methods have been developed to facilitate teeth movement utilizing clear, removable teeth aligners as an alternative to braces. A mold of the patient's bite is initially taken and desired ending positions for the patient's teeth (i.e., a functionally and aesthetically optimum position) are determined, based on a prescription provided by an orthodontist or dentist. Corrective paths between the initial positions of the teeth and their desired ending positions are then planned. These corrective paths generally include a plurality of intermediate positions between the initial and ending positions of the teeth. Multiple clear, removable aligners formed to move the teeth, to the various positions along the corrective path are then manufactured. One system for providing such aligners formed to move the teeth to the various positions along the corrective path is the Invisalign® System from Align Technologies, Inc. of Santa Clara, Calif.

In currently available systems for providing clear, removable tooth aligners, it is often necessary to manually manipulate digital and/or physical models of a patient's teeth to plan movements of the teeth through their various treatment stages, and, thus, to manufacture the corresponding stages of aligners. Although some aspects of the planning and manufacturing processes have been automated, one continuing technical challenge has been to further automate these processes. This challenge is difficult to overcome, primarily because every patient's teeth are unique and their movements during treatment are also unique. In a tooth moving treatment involving multiple clear, removable aligners, every aligner made is different from every other aligner, not only for one patient but, of course, from patient to patient as

2

well. Therefore, automating treatment planning and aligner manufacturing is extremely challenging. At the same time, manually planning each stage of treatment is quite labor and time intensive and requires extensive training.

Therefore a need clearly exists for apparatus, systems, and methods to increase automation of a tooth movement treatment planning process. Ideally, such automation would reduce the time and resources needed to stage the movement of teeth during an alignment treatment. At least some of these objectives will be met by the present invention.

SUMMARY

Embodiments of the present invention provide apparatus, systems, and methods for automated staging of teeth, from an initial position to a final, corrected position. Depending upon the particular needs of the patient, the patient's teeth are scheduled to move according to various movement patterns, routes, rates, and/or distances; and the need for utilizing tooth staggering, round-tripping, and/or slowing techniques. Furthermore, the invention provides techniques for minimizing the treatment period of the patient based upon the pattern, route, rate, and/or distance selected for the patient's individual needs, as well as the need for any tooth staggering, round-tripping and/or slowing technique(s).

BRIEF DESCRIPTION OF THE DRAWINGS

A more complete understanding of the present invention may be derived by referring to the detailed description and claims when considered in connection with the drawing Figures, where like reference numbers refer to similar elements throughout the Figures, and:

FIG. 1A is a diagram showing the arrangement of a patient's teeth at an initial stage of orthodontic treatment. FIG. 1B is a diagram showing the arrangement of a patient's teeth at an intermediate stage of orthodontic treatment. FIG. 1C is a diagram showing the arrangement of a patient's teeth at a final stage of orthodontic treatment;

FIG. 1D is a diagram showing teeth numbering according to the standard system of tooth numbering;

FIG. 2A is a diagram illustrating a partial model of a patient's dentition, including a model of gingival tissue;

FIG. 2B is a flow diagram illustrating a plurality of patterns and options available to a computing device for optimizing the movement of a patient's teeth during treatment;

FIG. 3 is a diagram of an exemplary embodiment of an "all-equal" pattern for moving the teeth of a patient during an orthodontic treatment;

FIG. 4 is a diagram of one exemplary embodiment of an "A-shaped" pattern for moving the gapped teeth of a patient during an orthodontic treatment;

FIG. 5 is a diagram of an exemplary embodiment of a "V-shaped" pattern for moving the crowded teeth of a patient during an orthodontic treatment;

FIG. 6A is a diagram of one exemplary embodiment of a "Mid-Line Shift" pattern for moving the skewed teeth of a patient during an orthodontic treatment;

FIG. 6B is a diagram of an exemplary embodiment of another "Mid-Line Shift" pattern for moving the skewed teeth of a patient during an orthodontic treatment;

FIG. 7 is a diagram of one exemplary embodiment of an "M-shaped" pattern for moving the gapped teeth of a patient during an orthodontic treatment;

US 10,524,879 B2

3

FIG. 8 is a diagram of the exemplary embodiment of FIG. 4 utilizing a staggering technique to avoid collisions with and/or obstructions between teeth during the orthodontic treatment;

FIG. 9 is a diagram of the exemplary embodiment of FIG. 4 utilizing a round-tripping technique to avoid collisions with and/or obstructions between teeth during the orthodontic treatment;

FIG. 10A is a diagram of the exemplary embodiment of FIG. 5 utilizing interim keyframes to avoid collisions with and/or obstructions between teeth during the orthodontic treatment;

FIG. 10B is a diagram of the exemplary embodiment of FIG. 5 utilizing different rates of movement to avoid collisions with and/or obstructions between teeth during the orthodontic treatment; and

FIG. 11 is flow diagram of a method for scheduling the movement of teeth during an orthodontic treatment.

DETAILED DESCRIPTION OF THE INVENTION

U.S. patent application Ser. No. 09/169,276, now abandoned; U.S. patent application Ser. Nos. 09/264,547; and 09/311,716, now U.S. Pat. No. 6,514,074 describe techniques for generating 3-dimensional digital data sets containing models of individual components of a patient's dentition. These data sets include digital models of individual teeth and the gingival tissue surrounding the teeth. Furthermore, these applications also describe computer-implemented techniques for using the digital models in designing and simulating an orthodontic treatment plan for the patient. For example, one such technique involves receiving an initial data set that represents the patient's teeth before treatment, specifying a desired arrangement of the patient's teeth after treatment, and calculating transformations that will move the teeth from the initial to the final positions over desired treatment paths. U.S. patent application Ser. No. 09/169,276 also describes the creation of data sets representing the tooth positions at various treatment stages and the use of these data sets to produce orthodontic appliances that implement the treatment plan. One technique for producing an orthodontic appliance involves creating a positive mold of the patient's dentition at one of the treatment stages and using a conventional pressure molding technique to form the appliance around the positive mold. A design of orthodontic appliances from the digital dentition models is, for example, described in U.S. patent application Ser. No. 09/169,034.

FIGS. 1A, 1B, and 1C show a patient's dentition 100 at three stages during a course of treatment. FIG. 1A illustrates the initial positions of the patient's teeth before treatment begins. A digital model of the teeth at these initial positions is captured in an initial digital data set (IDDS). The digital model contained in the IDDS also includes portions representing gingival tissue surrounding the patient's teeth. A computer program segments the IDDS into digital models of individual teeth and the gingival tissue.

FIG. 1B illustrates an example of how the patient's teeth may be oriented at an intermediate stage in the treatment process, and FIG. 1C illustrates an example of how the patient's teeth may be oriented at their final positions. A human operator and/or a computer program manipulate the digital models of the patient's teeth to achieve the final tooth positions. The program then calculates one or more of the intermediate positions, taking into account any constraints imposed on the movement of the teeth by the human

4

operator or by the natural characteristics of the teeth themselves. The program also accounts for any collisions that might occur between teeth as the teeth move from one treatment stage to the next. Selecting the final and intermediate tooth positions and the treatment paths along which the teeth move is described in more detail in one or more of the patent applications discussed above, which are all hereby incorporated by reference, in their respective entireties.

FIG. 1D is a diagram of a set of teeth showing the standard system of numbering teeth. Reference is made to this standard system of numbering throughout the discussion below.

FIG. 2A is a diagram illustrating a portion of a typical digital dentition model 110 derived from the IDDS. Dentition model 110 includes models of individual teeth 120 and a model of the patient's gums 140. Various techniques for creating models of gum tissue and individual teeth from the IDDS are described in, for example, U.S. patent application Ser. Nos. 09/264,547 and 09/311,941.

Furthermore, FIG. 2A shows a portion of another gingival model 200 (a "secondary" gingival model), which is constructed to overlies gingival model 140 derived from the IDDS (the "primary" gingival model). The program uses the secondary gingival model 200 to model the deformation of the gingival tissue around the patient's teeth as the teeth move from their initial positions to their final positions. This ensures that orthodontic appliances made from positive molds of the patient's dentition fit comfortably around the patient's gums at all treatment stages. The secondary gingival model 200 also adds thickness to the gum model, which ensures that the orthodontic appliances do not press too tightly against the patient's gums.

Reference will now be made to various exemplary embodiments of the invention, which are illustrated in the accompanying figures. While these exemplary embodiments are described in sufficient detail to enable those skilled in the art to practice the invention, it should be understood that other embodiments may be realized and that logical and/or mechanical changes may be made without departing from the spirit and scope of the invention. Thus, the various embodiments herein are presented for purposes of illustration and not by way of limitation. For example, the steps recited in any of the method or process descriptions may be executed in any order and are not limited to the order presented. Moreover, any of the functions or steps may be outsourced to or performed by one or more third parties.

For the sake of brevity, conventional data networking, application development, and other functional aspects of the systems (and components of the individual operating components of the systems) may not be described in detail herein. Furthermore, the connecting lines shown in the various figures contained herein are intended to represent exemplary functional relationships and/or physical connections between the various elements. It should be noted that many alternative and/or additional functional relationships or physical connections may be present in a practical system.

Various embodiments of the present invention include one or more computing devices having programs stored therein for staging the movement of a patient's teeth. The computing device(s) or various components of any computing device discussed herein may include one or more of the following: a host server or other computing systems including a processor for processing digital data; a memory coupled to the processor for storing digital data; an input digitizer coupled to the processor for inputting digital data; an application program stored in the memory and accessible by the processor for directing processing of digital data by

US 10,524,879 B2

5

the processor; a display device coupled to the processor and memory for displaying information derived from digital data processed by the processor; and a plurality of databases. Various file indexes and/or databases used herein may include: client data; merchant data; and/or other similar useful data.

As those skilled in the art will appreciate, any computing device utilized by a user may include an operating system (e.g., Windows NT, 95/98/2000, OS2, UNIX, Linux, Solaris, MacOS, etc.) as well as various conventional support software and drivers typically associated with computers. As will be appreciated by one of ordinary skill in the art, each computing device may be embodied as a customization of an existing system, an add-on product, upgraded software, a stand alone system, a distributed system, a method, a data processing system, a device for data processing, and/or a computer program product. Accordingly, any program stored therein may take the form of an entirely software embodiment, an entirely hardware embodiment, or an embodiment combining aspects of both software and hardware. Furthermore, any program may take the form of a computer program product on a computer-readable storage medium having computer-readable program code means embodied in the storage medium. Any suitable computer-readable storage medium may be utilized, including hard disks, CD-ROM, optical storage devices, magnetic storage devices, and/or the like.

In accordance with one exemplary embodiment, a computing device is configured to receive an electronic representation of the patient's teeth in an initial position taken by, for example, an intra-oral scanner (i.e., a CT scanner) based on an impression or partial impression of the patient's teeth. In addition, the computing device is configured to receive or generate an electronic representation of a desired final position for each of the patient's teeth. The program stored within the computing device is configured to analyze the initial and final positions, and automatically create a route for each tooth to move from its initial position to its final position. A set of aligners to move the teeth along the route in various stages is manufactured. In doing such, the program is configured to coordinate the movement of the teeth such that the simplest method of moving teeth is utilized based upon several factors (e.g., complexity of movement required, obstructions from other teeth, and the like).

FIG. 2B is a flow diagram illustrating a plurality of patterns and options available to a system user and a computing device for optimizing the movement of a patient's teeth during treatment. After the computing device generates the electronic representation of the patient's teeth with respect to the desired final position, in accordance with an exemplary embodiment, the system user can decide which pattern, or combination of patterns thereof, to suitably utilize for moving the patient's teeth to achieve the desired final position, for example, by determining whether the patient's teeth does not require complex movements, and/or has gaps, crowding or are otherwise skewed. The computer program then calculates the planned stages in between the current and desired final position. If the patient does not require complex movements, an "all-equal" pattern **300** (discussed below) of teeth movement can be selected by the system user and utilized by the program. For patients having too much space between teeth (i.e., gaps between teeth), the system user can enable the program to be configured to utilize an "A-shaped" pattern **400** (discussed below) to coordinate the movement of the patient's teeth. For the opposite case (i.e., crowded teeth), the system user can enable the program to be configured to utilize a "V-shaped"

6

pattern **500** (discussed below) to coordinate the movement of the patient's teeth. If a patient's teeth are skewed to the left or right of the patient's mid-line, a "Mid-Line Shift" pattern **600** (discussed below) for small shifts or a Mid-Line Shift pattern **600'** (discussed below) can be selected by the system user to enable the program to coordinate the staged movement of the patient's teeth. For a set of teeth having gaps between both posterior and anterior teeth, the system user can enable the program to be configured to utilize an "M-shaped" pattern **700** (discussed below) to coordinate teeth movement. In addition, any other treatment patterns can be suitably selected from other orthodontic treatment patterns for treating space closure, reproximation, dental expansion, flaring, distalization, and/or lower incisor extraction, such as those patterns disclosed in U.S. Pat. No. 6,729,876, entitled "Tooth Path Treatment Plan" issued on May 4, 2004 and assigned to Align Technology, Inc.

Selection of a pattern, e.g., patterns for addressing all equal, gapped, crowded or skewed teeth, can be suitably determined by the system user through use of one or more command or input screens of a computing device. For example, in accordance with an exemplary embodiment, a computing device can be configured to allow the system user to assess the initial and desired final positions of a patient's teeth and then suitably select from such command screens appropriate movement patterns, as well as the extent or degree of stages within any pattern and/or the severity of the teeth misalignment, the speed of movement during treatment for each of the teeth and other treatment criteria. Such a configuration can include various known orthodontic treatment protocols, or any devised hereinafter.

While an exemplary embodiment may be configured to have a system user select a suitably pattern for treatment, in accordance with another exemplary embodiment, the computer program can be suitably configured to determine and select such a pattern. For example, by measuring distances of movement needed and/or otherwise analyzing the electronic representation of the patient's teeth in initial and final positions, and then based on algorithms to determine whether the teeth need approximately all-equal movement, or whether the teeth are gapped, crowded or skewed, or some combination thereof, the computer program can select a suitable pattern for treatment planning.

After the system user and/or computer program has decided which pattern to utilize, the system user can determine, and/or computer program is configured to determine, if the pattern should be modified to accommodate the teeth movement of the current patient to avoid collision. In accordance with an exemplary embodiment, to determine whether a collision is likely, the computer program can suitably calculate distances between a first tooth and a second tooth and then apply geometrical techniques, such as those disclosed in disclosed in U.S. Pat. No. 6,729,876, entitled "Tooth Path Treatment Plan" issued on May 4, 2004 and assigned to Align Technology, Inc.

In one embodiment, the program is configured to "stagger", "round trip" and/or slow the movement (each of which is discussed below, respectively) of one or more teeth if the patient's teeth cannot be moved without colliding with and/or obstructing another tooth/teeth. Based on that assessment, the program determines the most efficient path to take through some combination of patterns and accommodation of movement thereof.

As discussed above, for patients that do not require complex tooth movement coordination between multiple teeth or for teeth needing relatively simple correction, the program is configured to utilize an "all-equal" pattern in

US 10,524,879 B2

7

staging a set of aligners to correct the teeth. In accordance with one exemplary embodiment of the invention, the “all-equal” pattern provides that all of a patient’s teeth move in parallel with one another. In other words, all of the patient’s teeth that need to move begin moving at the same stage, and finish moving at the same stage.

Since each tooth begins and ends at the same stage, and the distance each tooth needs to travel may differ, the rate at which each tooth will move will generally vary. Specifically, the rate at which any one tooth will move generally depends upon how many total stages are needed to treat the patient, wherein the total number of stages needed for the treatment is the number of stages needed to place all of the teeth in their respective final positions. As such, the total number of stages needed for treatment is the number of stages needed for the tooth requiring the greatest number of stages for it to reach its final position. For example, if a first tooth needs five stages (at its maximum rate) of to reach its final position, a second tooth needs nine stages (at its maximum rate) to reach its final position, and a third tooth needs seven stages (at its maximum rate) to reach its final position, the total number of stages needed for treatment is nine stages. Moreover, the rate of the first and third teeth will generally be reduced, respectively, to accommodate the increased number of stages. As such, the first tooth will move at a rate of approximately five-ninths ($\frac{5}{9}$) its maximum rate, and the third tooth will move at a rate of seven-ninths ($\frac{7}{9}$) its maximum rate. Thus, each of these teeth will reach their final position at the same stage (i.e., stage 9).

The system user and/or program can suitably select a rate of tooth movement for each stage, such as by system user input on a command screen, or by computer algorithm. In accordance with one exemplary embodiment, the maximum rate at which a tooth can move is approximately 0.25 millimeters per stage (mm/stage), based in part upon physical limitations of movement of the certain teeth, such as the incisors. However, this maximum rate is capable of being higher or lower depending upon the patient’s comfort level and/or tolerance for pain. In other words, the maximum rate at which the teeth move should be such that it does not cause significant discomfort or pain to the patient, but allows fast, efficient movement. The minimum rate can be any rate greater than zero, with the understanding that slower rates mean more stages and longer treatment times.

FIG. 3 is a diagram representing one example of an “all-equal” pattern 300 for moving the teeth of a patient in accordance with one exemplary embodiment of the invention. Column 310 depicts the number of stages for this particular treatment (i.e., stage 0 through stage 8), wherein stage 0 represents the patient’s current teeth positioning, and stage 8 represents the final teeth positioning (or a final desired position for each respective tooth). The remaining columns depict the tooth number 320 according to the standard tooth numbering system, and the position number 330 (i.e., the relative position of each tooth on the patient’s jaw arch). Notably, for illustration purposes it is assumed that the patient is not missing any teeth.

Recall, each tooth in an “all-equal” pattern is configured to be moved at the same time and for the same number of stages. Tooth movement is represented by the solid line connecting the teeth from their initial position (i.e., stage 0) to their final position (i.e., stage 8). Thus, FIG. 3 depicts each of teeth 18 through 31 moving at the same time through stages through 7 until they reach their desired final position at stage 8.

For a set of teeth having gaps between at least two posterior teeth, the program is configured to utilize an

8

“A-shaped” pattern in staging a set of aligners to correct the teeth. In accordance with one exemplary embodiment of the invention, the “A-shaped” pattern provides that teeth having the same and/or similar positions on the arch will be moved beginning at the same stage, and will move continuously until they reach their final position. Moreover, the “A-shaped” pattern begins by moving the most anterior-positioned teeth (e.g., the incisors, or teeth in positions 1 and/or 2) then sequentially moving the next posterior-positioned teeth until all of the teeth reach their final position. In accordance with an exemplary embodiment, the next posterior-positioned teeth are not scheduled to begin moving until at least approximately the half-way stage of its respective anterior-positioned teeth. For this and any of the other treatment patterns below, allowing movement of numerous teeth significantly earlier than half-way can result in undesirable pain, particularly in larger teeth, and attempting to move teeth too fast can cause the teeth to lose anchorage as well. On the other hand, allowing movement significantly later than approximately half-way delays treatment by increasing the total number of stages, and thus aligners needed. In accordance with an aspect of one exemplary embodiment, no more than two posterior teeth on one side of the arch may move simultaneously. In the event it is determined that the teeth may collide, such as the incisors if they move at the same time, then the movement of the incisors may be “staggered”, “round-tripped”, and/or include slower rates of movement (discussed below) to prevent them from colliding with and/or obstructing one another.

For example, a set of incisors may need six stages to move from their starting position to their final position. This means that the patient’s pair of canines will not begin moving until at least approximately the incisors’ stage 3. Furthermore, the patient’s bicuspid are not scheduled to begin moving until the canines’ stage 2 since the canines need 3 stages to move. This staging process continues until all of the patient’s teeth reach their final position.

In accordance with one exemplary embodiment, the maximum rate at which the incisors may be configured to move is approximately 0.25 mm/stage, and the maximum rate at which the remaining teeth may be configured to move is approximately 0.33 mm/stage. However, similar to above, these maximum and/or selected rates are capable of being higher and/or lower depending upon the patient’s comfort level and/or tolerance for pain.

FIG. 4 is a diagram illustrating an example of an “A-shaped” pattern 400 in accordance with one exemplary embodiment of the invention. Similar to above, Column 410 illustrates the number of stages needed to correct the patient’s teeth. In this example, the patient requires 18 stages of treatment before the patient’s teeth reach their final position in stage 19. Moreover, similar to FIG. 3, FIG. 4 uses the standard teeth numbering system 420 to identify each of the teeth and a position 430 to illustrate the respective positioning of the teeth on the patient’s arch.

Pattern 400 initiates by moving teeth 7, 8, 9, and 10 (i.e., the incisors) in stage 1. These teeth move in stages 1 through 8 to reach their final position in stage 9, but are not moved in stages 9 through 19. The solid lines represent the movement of teeth 7, 8, 9, and 10 in stages 1 through 8, and the lack of such solid lines in stages 9 through 19 represent the non-movement of teeth 7, 8, 9, and 10. Notably, the black boxes represent initial or final tooth positions, wherein no tooth movement occurs.

Next, the teeth in position 3 (i.e., teeth 6 and 11) are moved in stages 5 through 8, but are not moved in stages 1

US 10,524,879 B2

9

through 4 or in stages 9 through 19. Teeth 6 and 11 are not scheduled to move until at least approximately the middle stage (i.e., stage 4) of the previous tooth movement. In other words, teeth 7 through 11 move a total of 8 stages and teeth 6 and 11 are not scheduled to move prior to stage 4 of those 8 stages.

After the teeth in position 3 have moved at least half way (i.e., 2 stages), the teeth in position 4 (i.e., teeth 5 and 12) are scheduled to begin moving. Teeth 5 and 12 are scheduled to begin moving no sooner than in stage 7 and continue moving until their final position in stage 11. In one embodiment, teeth 5 and 12 do not move in stages 1 through 7, or in stages 11 through 19.

The teeth in position 5 (i.e., teeth 4 and 13) are the next teeth scheduled to move in pattern 400, but no sooner than the middle stage (i.e., stage 9) for the teeth in position 4. Teeth 4 and 13 are scheduled to begin moving in stage 10 and continue to move until reaching their final position in stage 15. In one embodiment, teeth 4 and 13 do not move in stages 1 through 9, or in stages 15 through 19.

Next, the teeth in position 6 (i.e., teeth 3 and 14) are scheduled to move, but no sooner than the half way point (i.e., stage 12 or later) of the teeth in position 5. Teeth 3 and 14 are scheduled to begin moving in stage 13 and continue to move until reaching their final position in stage 16. Furthermore, similar to above, teeth 3 and 14 do not move in stages 1 through 12, or in stages 16 through 19.

Final teeth movement in pattern 400 is scheduled to begin no earlier than in stage 14 for teeth in position 7 (i.e., teeth 2 and 15). Teeth 2 and 15 are scheduled to begin movement in stage 16 and continue to move until reaching their final position in stage 19. Moreover, teeth 2 and 15 do not move in stages 1 through 15.

For a set of teeth lacking space in between at least two teeth (i.e., over-crowding), the program is configured to utilize a “V-shaped” pattern in staging a set of aligners to correct the teeth. In accordance with one exemplary embodiment of the invention, the “V-shaped” pattern provides that teeth having the same and/or similar positions on the arch will be moved beginning at the same stage, and will move continuously until they reach their final position. Moreover, the “V-shaped” pattern begins by moving the most posterior-positioned teeth (e.g., the molars, or teeth in position 7 and/or 8) then sequentially moving the next anterior-positioned teeth until all of the teeth reach their final position. The next anterior-positioned teeth are not scheduled to begin moving until at least approximately the half-way stage of its respective posterior-positioned tooth. In accordance with an aspect of one exemplary embodiment, no more than two posterior teeth on one side of the arch may move simultaneously, but all of the incisors move simultaneously during the final stages of the treatment. In one embodiment, if the teeth, e.g., incisors, will collide if they move at the same time, then the teeth may be “staggered”, “round-tripped”, and/or slowed (discussed below) to prevent them from colliding with one another.

In accordance with one exemplary embodiment, the maximum rate at which the incisors move may be configured to be approximately 0.25 mm/stage, and the maximum rate at which the remaining teeth move may be configured to be approximately 0.33 mm/stage. However, similar to above, these maximum and/or selected rates are capable of being higher or lower depending upon the patient’s comfort level and/or tolerance for pain.

FIG. 5 is a diagram illustrating an example of a “V-shaped” pattern 500 in accordance with one exemplary embodiment of the invention. Similar to above, column 510

10

illustrates the number of stages needed to correct the patient’s teeth. In this example, the patient requires 20 stages of treatment before the patient’s teeth reach their final position in stage 21. Moreover, similar to FIGS. 3 and 4, FIG. 5 uses the standard teeth numbering system 520 to identify each of the teeth and a position 530 to illustrate the respective positioning of the teeth on the patient’s arch.

Pattern 500 initiates by moving teeth in position 7 (i.e., the molars numbered as teeth 2 and 15) in stage 1. These teeth continue to move in stages 1 through 6 to reach their final position in stage 7, but are not moved in stages 8 through 21. Next, the teeth in position 6 (i.e., teeth 3 and 14) are moved in stages 4 through 10, but are not moved in stages 1 through 3 or in stages 10 through 21. In one embodiment, teeth 3 and 14 are not scheduled to move until at least approximately the middle stage (i.e., stage 3) of the previous tooth movement. In other words, teeth 2 through 15 move a total of 6 stages, and teeth 3 and 14 are not scheduled to begin moving their seven stages prior to stage 3 of teeth 2 and 15’s 6 stages.

In this example, the patient does not need the teeth in position 5 (i.e., teeth 4 and 13) to move. Thus, after the teeth in position 6 have moved half way (i.e., 4 stages), the teeth in position 4 (i.e., teeth 5 and 12) are scheduled to begin moving. Teeth 5 and 12 are scheduled to begin moving no sooner than in stage 7 and continue moving until their final position in stage 12. In one embodiment, teeth 5 and 12 do not move in stages 1 through 7, or in stages 13 through 21.

The teeth in position 3 (i.e., teeth 6 and 11) are the next teeth scheduled to move in pattern 500, but no sooner than the middle stage (i.e., stage 10) for the teeth in position 4. Teeth 6 and 11 begin moving in stage 11 and continue to move until reaching their final position in stage 19. In one embodiment, teeth 6 and 11 do not move in stages 1 through 10, or in stages 19 through 21.

Final teeth movement in pattern 500 is scheduled to begin no earlier than in stage 14 for teeth in positions 2 and 1 (i.e., the incisors numbered as teeth 7, 8, 9, and 10). Teeth 7 through 10 are scheduled to begin movement in stage 15 and continue to move until reaching their final position in stage 21. Similar to above, teeth 7 through 10 do not move in stages 1 through 14.

For a set of teeth that is off-centered (i.e., skewed to one side), the program is configured to utilize a “mid-line shift” pattern in staging a set of aligners to correct the teeth. In accordance with one exemplary embodiment of the invention, the mid-line shift pattern provides that tooth movement begins on one side of the patient’s arch to center the teeth with respect to the mid-line of the patient’s mouth. The next tooth/teeth to move is/are not scheduled to begin moving until at least approximately the half way stage of its respective previously-scheduled tooth/teeth. For example, if the patient’s teeth are skewed to the left, tooth movement begins by moving the most-posterior tooth on the right side of the patient’s arch to the right, and then progressively shifting the teeth towards the right filling in the space vacated by the previously-moved tooth. The opposite is true for teeth skewed to the right.

For situations where the patient’s teeth need to shift less than about 1.0 mm, in one embodiment of the invention, the incisors move simultaneously during an intermediate stage of the treatment. In one embodiment, if the incisors will collide and/or obstruct one another if they move at the same time, then the incisors may be “staggered”, “round-tripped”, and/or slowed (discussed below) to prevent them from doing such. In another embodiment of the invention, when the patient’s mid-line needs to shift greater than about 1.0 mm,

US 10,524,879 B2

11

each of the incisors is scheduled to move independent of the other incisors. In yet another exemplary embodiment of the invention, no more than two posterior teeth on one side of the arch may move simultaneously regardless of the amount of shift required.

In accordance with one exemplary embodiment of the invention, the maximum rate at which the incisors move may be configured to be approximately 0.25 mm/stage, and the maximum rate at which the remaining teeth move may be configured to be approximately 0.33 mm/stage. However, similar to above, these maximum and/or selected rates are capable of being higher or lower depending upon the patient's comfort level and/or tolerance for pain.

FIG. 6A is a diagram illustrating an example of a "mid-line shift" pattern **600** for teeth skewed (to the patient's left) less than about 1.0 mm in accordance with one exemplary embodiment of the invention. Similar to above, column **610** illustrates the number of stages needed to correct the patient's teeth. In this example, the patient requires 26 stages of treatment before the patient's teeth reach their final position in stage 27. Moreover, similar to FIGS. 3-5, FIG. 6A uses the standard teeth numbering system **620** to identify each of the teeth and a position **630** to illustrate the respective positioning of the teeth on the patient's arch.

Pattern **600** initiates by moving tooth 2 to the right in stage 1. Next, tooth 3 is moved to the right for 2 stages, followed by tooth 4 moving to the right for 2 stages. Tooth 5 moves next for 3 stages, followed by tooth 6 for 4 stages. The incisors (i.e., teeth 7 through 10) are scheduled to move next beginning in stage 11 (although they could have been scheduled as early as stage 10). As noted above, since the patient needs a mid-line shift less than about 1.0 mm, the incisors move together. The remaining teeth continue shifting sequentially to the right until all the teeth arrive in their respective final position in stage 27.

In one embodiment, the teeth are not scheduled to move after they have reached their respective final positions. Furthermore, the next tooth/teeth scheduled to move are not scheduled to move prior to at least approximately the half-way stage of the previously-scheduled tooth/teeth.

FIG. 6B is a diagram illustrating an example of an "mid-line shift" pattern **600'** for teeth skewed (to the patient's right) more than about 1.0 mm in accordance with one exemplary embodiment of the invention. Similar to above, column **610** illustrates the number of stages needed to correct the patient's teeth. In this example, the patient requires 29 stages of treatment before the patient's teeth reach their final position in stage 30. Moreover, similar to FIG. 6A, FIG. 6B uses the standard teeth numbering system **620** to identify each of the teeth and a position **630** to illustrate the respective positioning of the teeth on the patient's arch.

Pattern **600** initiates by moving tooth 15 to the left 3 stages beginning in stage 1. Next, tooth 14 is moved to the left for 3 stages, followed by tooth 13 moving to the left for 3 stages. The remaining teeth continue shifting sequentially to the left until all the teeth arrive in their respective final position in stage 30. As noted above, since the patient needs a mid-line shift greater than about 1.0 mm, the incisors do not move together, but instead move individually. In one embodiment, the teeth are not scheduled to move after they have reached their respective final positions. Furthermore, the next tooth scheduled to move is not scheduled to move prior to at least approximately the halfway stage of the previously-scheduled tooth.

For a set of teeth having gaps between posterior teeth and anterior teeth, the program is configured to utilize an "M-shaped" pattern in creating a set of aligners to correct the

12

teeth. In accordance with one exemplary embodiment of the invention, the "M-shaped" pattern provides that teeth having the same and/or similar positions on the arch will be moved beginning at the same stage, and will move continuously until they reach their final position. Moreover, the "M-shaped" pattern begins by moving teeth between the anterior teeth and the posterior teeth (e.g., the bicuspid, or teeth in positions 4 and/or 5) then sequentially moving both the adjacent anterior and/or adjacent posterior teeth until all of the teeth reach their final position. Furthermore, the teeth, e.g., incisors, move simultaneously unless they will collide with or obstruct one another, wherein the incisors may be "staggered", "round-tripped", and/or slowed (discussed below) to prevent them from colliding with one another. In addition, similar to embodiments discussed above, subsequently scheduled teeth are not scheduled to begin moving until at least approximately the half-way stage of its respective precedent tooth. Moreover, the corresponding positions on each side of the patient's arch move during the same stage. In accordance with an aspect of one exemplary embodiment, no more than two posterior teeth on one side of the arch may move simultaneously.

In accordance with one exemplary embodiment, the maximum rate at which the incisors move may be configured to be approximately 0.25 mm/stage, and the maximum rate at which the remaining teeth move may be configured to be approximately 0.33 mm/stage. However, similar to above, these maximum and/or selected rates are capable of being higher or lower depending upon the patient's comfort level and/or tolerance for pain.

FIG. 7 is a diagram illustrating an example of an "M-shaped" pattern **700** in accordance with one exemplary embodiment of the invention. Similar to above, column **710** illustrates the number of stages needed to correct the patient's teeth, wherein, in this example, the patient requires 16 stages of treatment before the patient's teeth reach their final position in stage 17. Moreover, similar to FIGS. 3-6B, FIG. 7 uses the standard teeth numbering system **720** to identify each of the teeth and a position **730** to illustrate the respective positioning of the teeth on the patient's arch.

Pattern **700** initiates by moving teeth in positions 5 and 6 (i.e., the bicuspid) in stage 1. These teeth continue to move until they reach their final position, which, for example includes teeth 5 and 12 moving in stages 1 through 6, and teeth 4 and 13 moving in stages 1 through 8. Notably, these teeth need different numbers of stages to reach their final positions. As such, their respective adjacent teeth are scheduled to begin moving during different stages.

In the example illustrated in FIG. 7, teeth 5 and 12 need five stages of treatment, thus, teeth 6 and 11 are scheduled to begin moving at the mid-point (i.e., stage 3) of teeth 5 and 12's treatment. Similarly, teeth 4 and 13 need seven stages, thus, teeth 3 and 14 are not scheduled to begin movement until stage 4 of teeth 4 and 13's treatment. Subsequently, the next adjacent teeth are scheduled to move proximate the mid-point of stages of its respective adjacent tooth.

In accordance with one exemplary embodiment, the maximum rate at which the incisors move may be configured to be approximately 0.25 mm/stage, and the maximum rate at which the remaining teeth move may be configured to be approximately 0.33 mm/stage. However, similar to above, these maximum and/or selected rates are capable of being higher or lower depending upon the patient's comfort level and/or tolerance for pain.

As referenced above, in cases where teeth may collide with or obstruct one another during movement, the program is configured to suitably stagger, slow down and/or plan-

US 10,524,879 B2

13

round-tripping for the teeth movement. “Staggering” is the process of delaying one or more teeth from moving one or more stages where it would otherwise move in order to prevent another tooth from colliding with and/or obstructing the path of the delayed tooth. “Slowing down” is the process of having one or more teeth scheduled to move at a rate less than the rate of other teeth, or even stopping using interim key frames, so that collisions and/or obstructions do not occur. “Round-tripping” is the technique of moving a first tooth out of the path of a second tooth, and once the second tooth has moved sufficiently, moving the first tooth back to its previous position before proceeding to a desired final position of that first tooth. Such staggering, slowing down and/or round-tripping can be suitably applied alone or in combination, and in any order. In an exemplary embodiment, the computer program first attempts staggering of the teeth movement, followed by slowing-down/interim key frames if the staggering does not avoid collisions, and then followed by round-tripping as a last resort. In addition, each of staggering, slowing down and round-tripping techniques can be applied to any of the patterns discussed above, or any other movement patterns hereinafter developed in the field of orthodontics.

FIG. 8 illustrates an example of the incisors of an “A-shaped” pattern 800 similar to the example of FIG. 4 with the teeth in position 1 (i.e., teeth 8 and 9) being staggered such that they do not collide with the teeth in position 2 (i.e., teeth 7 and 10). In this example, teeth 7 and 10 are scheduled to begin movement in stage 1. In a typical “A-shaped” pattern, teeth 8 and 9 would also begin movement in stage 1. However, if this were performed for the patient of this example, tooth 8 would collide with tooth 7 and/or tooth 9. Likewise, tooth 9 would collide with tooth 8 and/or tooth 10. Thus, tooth 8 is not scheduled to begin moving until a later stage, e.g., stage 2, to prevent such a collision. Furthermore, tooth 9 is likewise not scheduled to begin movement until a later stage, e.g., stage 3, to prevent a collision with tooth 8 and/or tooth 10. By staggering the tooth movement, any tooth/teeth that may collide with another tooth is moved out of the path of other teeth to prevent any undesired collisions.

Notably, although the above example of staggering refers to the incisors, staggering techniques may be used to delay the movement of any tooth and/or teeth in order to prevent one or more teeth from colliding. Moreover, the remaining schedule for the other teeth in pattern 800 would be similar to the discussion above with respect to FIG. 4. Furthermore, the above staggering example is with reference to an “A-shaped” pattern, however, the above discussion is equally applicable to an “all-equal” pattern, a “V-shaped” pattern, a “Mid-Line Shift” pattern, and an “M-shaped” pattern.

In addition to staggering tooth movement, the program also includes the ability to avoid teeth from colliding with and/or obstructing one another utilizing round-tripping techniques, wherein a tooth is positioned of the path of another tooth, and then repositioned or otherwise redirected until a desired final position. In accordance with an exemplary embodiment, the round-tripping process can also include the use of interim key frames that comprise “just-in-time” stops of movement of a selected tooth or teeth for one or more stages.

FIG. 9 illustrates an example of the incisors of an “A-shaped” pattern 900 similar to the example of FIG. 4 with the teeth in position 2 (i.e., teeth 7 and 10) being moved out of the way of tooth 8 and tooth 9, respectively. Recall in FIG. 4, tooth 7 is scheduled to move 8 stages. In this

14

example, tooth 7 is moved out of the way of tooth 8 for 3 stages (i.e., stages 1 through 3), tooth 8 takes 4 stages to pass through tooth 7’s previous position (i.e., stages 4 through 7), tooth 7 is moved back 3 stages to return to its previous position (i.e., stages 8 through 10), and then tooth 7 is moved its originally scheduled 8 stages (i.e., stages 11 through 18) to reach its final position in stage 19.

Similarly, recall in FIG. 4 that tooth 9 is also scheduled to move 8 stages. In the example of FIG. 9, tooth 10 is moved out of the way of tooth 9 for 2 stages (i.e., stages 1 and 2), tooth 10 takes 4 stages to pass through tooth 10’s previous position (i.e., stages 3 through 6), tooth 10 is moved back 2 stages to return to its previous position (i.e., stages 7 and 8), and then tooth 10 is moved its originally scheduled 8 stages (i.e., stages 9 through 16) to reach its final position in stage 17.

Notably, although the above example of round-tripping refers to the incisors, round-tripping techniques may be used to delay the movement of any tooth and/or teeth in order to prevent one or more teeth from colliding with and/or obstructing one another. Moreover, the remaining schedule for the other teeth in pattern 900 would be similar to the discussion above with respect to FIG. 4. Furthermore, the above round-tripping example is with reference to an “A-shaped” pattern, however, the above discussion is equally applicable to an all-equal pattern, a “V-shaped” pattern, a “Mid-Line Shift” pattern, and an “M-shaped” pattern.

Another technique utilized to avoid teeth from colliding with and/or obstructing one another is to slow the rate of movement of one or more teeth. As discussed above, the teeth ideally move at a maximum rate for each stage to reduce the overall number of stages of the treatment. When it is appropriate, one or more teeth can be scheduled to move at a rate less than the maximum rate, while other teeth can move at a constant and/or increased rate, so that collisions and/or obstructions do not occur. In addition to decreasing the rate of movement, the slow down process can also include the use of interim key frames that comprise “just-in-time” stops of movement of a selected tooth or teeth for one or more stages.

For example, FIGS. 10A and 10B shows an example of varying rates of movement for the teeth, such as for the over-crowding of teeth using a V-shaped pattern as illustrated in FIG. 5. In this example, tooth 7 initially moves at a rate of 0.23 mm for each of stages 12 through 21, and then is slowed down to a rate of 0.16 mm for each of stages 22 through 27, then further slowed down to 0.15 mm for each of stages 28 through 31. Furthermore, the rate of movement for tooth 8 initially moves at a rate of 0.22 mm for 12 and 13, then sped up to a rate of 0.23 for each of stages 14 through 23, and then is further sped up to 0.24 mm for stages 24-31, before being slowed to 0.21 mm for each of stages 32 and 33. Thus, tooth 7 is slowed to a rate in which it will not collide and/or obstruct the movement of tooth 8 and/or other teeth during the tooth movement treatment.

Similarly, tooth 9 is scheduled to move at its maximum rate of 0.09 mm per stages for each of stages 12 and 13, then slightly sped up to 0.10 mm per stage for each of stages 14 through 27. Next, an interim key frame is applied through stages 28-31 of tooth 9 to stop all movement of tooth 9, before being increased back to a speed of 0.12 mm per stages for each of stages 32 and 33. Thus, tooth 9 is slowed to a rate in which it will not collide and/or obstruct the movement of tooth 8 and/or other teeth during the tooth movement treatment.

US 10,524,879 B2

15

In this example, certain of the teeth, e.g., teeth 3, 4, 5, 6, 8, 10 and 11 can be configured to move proximate their maximum rate per stage for each of their respective stages of movement, with very slight increases and/or decreases in speed along the way since these teeth will not collide or obstruct one another during tooth movement. One the other hand, the rates of movement of teeth 7, 10 and 8 (using an interim key frame) are slowed to avoid such collisions.

FIG. 11 is a flow diagram of one exemplary embodiment of a method 1100 to stage the movement of one or more teeth in accordance with one exemplary embodiment of the invention. Method 1100, in one embodiment, initiates by receiving an electronic representation of a patient's teeth in their initial positions (step 1110). Furthermore, method 1100 includes the step of receiving an electronic representation of the patient's teeth in a desired final position (step 1120).

In one exemplary embodiment of the invention, method 1100 includes the step of determining a schedule in which each tooth will move (step 1130). In accordance with an aspect of an exemplary embodiment, step 1130 includes the step of determining a route for each of the patient's teeth (step 1140). In another aspect of the invention, step 1130 includes the step of determining a rate each tooth will move (step 1150). Step 1130, in yet another aspect of the invention, includes the step of determining a distance each tooth will need to travel to reach its final position (step 1160).

Method 1100, in another exemplary embodiment of the invention, includes determining the optimum number of stages for a patient's treatment (step 1170). The optimum number of stages, in one embodiment, is determined based upon the determinations of step 1130 through step 1170. Furthermore, step 1170 includes factoring any staggering, slowing down/interim key framing, and/or round-tripping needed to place the patient's teeth in their desired final position. For example, in FIGS. 3-9 the optimum number of stages needed for these respective examples factored in the type of pattern needed, the rate, the path, the distance, staggering, slowing down/interim key framing, and/or round-tripping in determining the optimum number of stages for treating the patient's teeth. As one skilled in the art will recognize, the optimum number of stages will likely differ from patient to patient.

In one exemplary embodiment, determining the optimum number of stages includes determining the minimum number of stages needed for each respective tooth to be placed in its final, desired position. In another exemplary embodiment, the optimum number of stages is the largest number of the minimum stages needed to place the patient's teeth in their final, desired position. For example, a patient has three teeth that need to be moved during treatment, wherein the first tooth needs 4 stages to move to its final position, the second tooth needs 9 stages to move to its final position, and the third tooth needs 6 stages to move to its final position. Assuming each of these teeth is scheduled to begin moving at the same stage, the optimum number of stages is 9 since this is the minimum number of stages needed to place all of the teeth in their final position.

Benefits, other advantages, and solutions to problems have been described herein with regard to specific embodiments. However, the benefits, advantages, solutions to problems, and any element(s) that may cause any benefit, advantage, or solution to occur or become more pronounced are not to be construed as critical, required, or essential features or elements of any or all the claims or the invention. The scope of the present invention is accordingly to be limited by nothing other than the appended claims, in which reference to an element in the singular is not intended to mean "one

16

and only one" unless explicitly so stated, but rather "one or more." All structural, chemical, and functional equivalents to the elements of the above-described exemplary embodiments that are known to those of ordinary skill in the art are expressly incorporated herein by reference and are intended to be encompassed by the present claims.

What is claimed is:

1. A computer-implemented method comprising:

determining, by one or more computer processors, a schedule of movement for dental objects during treatment stages, the dental objects being based from output of a scanning device, wherein the schedule of movement indicates whether each of the dental objects moves during each of the treatment stages;

calculating, by one or more computer processors, a respective route from an initial position toward a final position for each of the dental objects during the treatment stages; and

modifying, by one or more computer processors, the schedule of movement to avoid a collision or obstruction between two of the dental objects on their respective routes, the modifying comprising:

delaying initial movement of one of the dental objects; and

round-tripping one of the dental objects.

2. The computer-implemented method of claim 1, wherein determining the schedule of movement comprises selecting a movement pattern from a plurality of predetermined movement patterns.

3. The computer-implemented method of claim 1, further comprising recalculating at least one of the respective routes based on the modified schedule of movement.

4. The computer-implemented method of claim 1, further comprising manufacturing at least two orthodontic aligners, each of the orthodontic aligners corresponding to a respective one of the treatment stages.

5. The computer-implemented method of claim 4, wherein the manufacturing comprises: fabricating a respective positive mold of the dental objects for at least two of the treatment stages; and thermoforming an orthodontic aligner over each respective positive mold.

6. The computer-implemented method of claim 1, wherein the round-tripping comprises: moving a first of the dental objects away from the respective route of a second of the dental objects; and moving the first dental object toward its respective final position after the second dental object has sufficiently traversed its respective route to avoid the collision.

7. The computer-implemented method of claim 1, wherein the round-tripping comprises:

moving a first of the dental objects away from the respective route of a second of the dental objects; and moving the first dental object toward its previous position.

8. The computer-implemented method of claim 1, wherein:

the determining of the schedule of movement comprises determining, by one or more computer processors, a total number of the treatment stages; and

the determining of the total number of the treatment stages comprises:

determining, by one or more computer processors, a respective minimum number of treatment stages for each of the dental objects; and

US 10,524,879 B2

17

selecting, by one or more computer processors, a largest of the respective minimum numbers of treatment stages as the total number of the treatment stages.

9. A non-transitory computer-readable medium comprising instructions that, when executed by one or more computer processors, cause at least one of the one or more computer processors to:

determine a schedule of movement for dental objects during treatment stages, the dental objects being based from output from a scanning device, wherein the schedule of movement indicates whether each of the dental objects moves during each of the treatment stages; calculate a respective route from an initial position toward a desired final position for each of the dental objects during the treatment stages; and modify the schedule of movement to avoid a collision or obstruction between two of the dental objects on their respective routes, the modifying comprising: delaying initial movement of one of the dental objects; and round-tripping one of the dental objects.

10. The medium of claim 9, wherein determining the schedule of movement comprises selecting a movement pattern from a plurality of predetermined movement patterns.

11. The medium of claim 9, wherein the instructions, when executed by the one or more computer processors, further cause at least one of the one or more computer processors to recalculate at least one of the respective routes based on the modified schedule of movement.

12. The medium of claim 9, wherein the instructions, when executed by the one or more computer processors, further cause at least one of the one or more computer processors to control manufacture of at least two orthodontic aligners, each of the orthodontic aligners corresponding to a respective one of the treatment stages.

13. The medium of claim 12, wherein the manufacture comprises:

fabricating a respective positive mold of the dental objects for at least two of the treatment stages; and thermoforming an orthodontic aligner over each of the respective positive molds.

14. The medium of claim 9, wherein:

the determining of the schedule of movement comprises determining a total number of the treatment stages; and the determining of the total number of the treatment stages comprises:

determining a respective minimum number of treatment stages for each of the dental objects; and selecting a largest of the respective minimum numbers of treatment stages as the total number of the treatment stages.

15. A computer-implemented method comprising:

determining, by one or more computer processors, a schedule of movement for dental objects during treatment stages, the dental objects being based from output of a scanning device, wherein the schedule of movement indicates whether each of the dental objects moves during each of the treatment stages;

calculating, by the one or more computer processors, a respective route from an initial position toward a final position for each of the dental objects during the treatment stages; and

modifying, by the one or more computer processors, the schedule of movement to avoid a collision or obstruction

18

between two of the dental objects on their respective routes, the modifying comprising:

determining, by the one or more computer processors, that the respective route of a first of the dental objects results in a collision or obstruction with a second of the dental objects;

altering, by the one or more computer processors in response to the determining, the schedule of movement by delaying initial movement of the first dental object;

determining, by the one or more computer processors, that the altered schedule of movement still results in a collision or obstruction involving the first dental object; and

altering, by the one or more computer processors after the determining that the altered schedule of movement still results in a collision or obstruction, the schedule of movement of the first dental object by moving the first dental object out of the path of the second dental object, and once the second dental object has moved sufficiently, moving the first dental object back to the first dental object previous position before proceeding to a desired final position of the first dental object.

16. The computer-implemented method of claim 15, further comprising recalculating at least one of the respective routes based on the modified schedule of movement.

17. The computer-implemented method of claim 15, further comprising manufacturing at least two orthodontic aligners, each of the orthodontic aligners corresponding to a respective one of the treatment stages.

18. The computer-implemented method of claim 17, wherein the manufacturing comprises:

fabricating a respective positive mold of the dental objects for at least two of the treatment stages; and thermoforming an orthodontic aligner over each of the respective positive molds.

19. The computer-implemented method of claim 15, wherein:

the determining of the schedule of movement comprises determining a total number of the treatment stages; and the determining of the total number of the treatment stages comprises:

determining, by one or more computer processors, a respective minimum number of treatment stages for each of the dental objects; and

selecting, by one or more computer processors, a largest of the respective minimum numbers of treatment stages as the total number of the treatment stages.

20. A non-transitory computer-readable medium comprising instructions that, when executed by one or more computer processors, cause at least one of the one or more computer processors to:

determine a schedule of movement for dental objects during treatment stages, the dental objects being based from output from a scanning device, wherein the schedule of movement indicates whether each of the dental objects moves during each of the treatment stages;

calculate a respective route from an initial position toward a final position for each of the dental objects during the treatment stages; and

modify the schedule of movement to avoid a collision or obstruction between two of the dental objects on their respective routes, the modifying comprising:

US 10,524,879 B2

19

determining that the respective route of a first of the dental objects results in a collision or obstruction with a second of the dental objects;

altering, in response to the determining, the schedule of movement by delaying initial movement of the first dental object;

determining that the altered schedule of movement still results in a collision or obstruction involving the first dental object; and

altering, after the determining that the altered schedule of movement still results in a collision or obstruction, the schedule of movement by round-tripping the first dental object.

21. The medium of claim **20**, wherein determining the schedule of movement comprises selecting a movement pattern from a plurality of predetermined movement patterns.

20

22. The medium of claim **20**, wherein the instructions, when executed by the one or more computer processors, further cause at least one of the one or more computer processors to recalculate at least one of the respective routes based on the modified schedule of movement.

23. The medium of claim **20**, wherein the instructions, when executed by the one or more computer processors, further cause at least one of the one or more computer processors to control manufacture of at least two orthodontic aligners, each of the orthodontic aligners corresponding to a respective one of the treatment stages.

24. The medium of claim **23**, wherein the manufacture comprises:

fabricating a respective positive mold of the dental objects for at least two of the treatment stages; and
thermoforming a respective one of the orthodontic aligners over each of the respective positive molds.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 10,524,879 B2
APPLICATION NO. : 15/834649
DATED : January 7, 2020
INVENTOR(S) : Ian Kitching, Alexander Dmitriev and Alexey Vishnevskiy

Page 1 of 2

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

In the Claims

Column 16, Line 15, Claim 1:

Please replace:

“obj ects”

With:

-- objects --

Column 16, Line 56, Claim 7:

Please replace:

“obj ects”

With:

-- objects --

Column 17, Line 19, Claim 9:

Please replace:

“obj ects”

With:

-- objects --

Column 17, Line 51, Claim 14:

Please replace:

“obj ects”

With:


-- objects --

Column 17, Line 57, Claim 15:

Please replace:

“obj ects”

Signed and Sealed this
Thirteenth Day of October, 2020



Andrei Iancu
Director of the United States Patent and Trademark Office

CERTIFICATE OF CORRECTION (continued)

Page 2 of 2

U.S. Pat. No. 10,524,879 B2

With:

-- objects --

Column 18, Line 63, Claim 20:

Please replace:

“obj ects”

With:

-- objects --

Column 18, Line 66, Claim 20:

Please replace:

“obj ects”

With:

-- objects --